



EAGLE TT AWD AIRCRAFT TUGS

TT-10 & TT-12

Engineered to meet the needs of today's regional airlines, corporate flight departments, fixed base operators and military flight operations, the Eagle TT series All Wheel Drive aircraft tow tractor packs a significant amount of value into a low profile, compact package.

Here is what the TT series has to offer:

- Only product in its towing capacity available in All Wheel Drive - providing safe, controlled traction on all surface conditions.
- Ergonomic operator compartment, low-profile design and mirror-less hitch visibility allow operators to safely and efficiently handle aircraft.
- Designed with carefully matched components, resulting in minimal or no unscheduled maintenance or repair.
- Unparalleled reliability and factory-direct service and support is the Eagle Tugs advantage.
- Eagle Tugs has 40 years of experience designing, building and supporting reliable tow tractors.



EAGLE TUGS

26111 Northline Rd
Taylor, MI 48180
800 671 0431 tel
734 442 1005 fax
www.eagletugs.com

GLOBAL SALES OFFICE

Maple House
High Street
Potters Bar
Herts, EN6 5BS
UK
+44 (0) 208 363 9528

STANDARD FEATURES

- All Wheel Drive*
- Low profile
- Hitch sight tunnels
- Power steering & braking
- Front & Rear brakes
- Side & top engine access
- Low oil/high temp shutdown system

RECOMMENDED OPTIONS

- Front + Rear E-hitch
- Limited slip differential
- Custom paint scheme
- 2,000 hour PM kit

TOWABLE AIRCRAFT

For a complete list, please consult factory or eagletugs.com.



EAGLE TUGS
 26111 Northline Rd
 Taylor, MI 48180
 800 671 0431 tel
 734 442 1005 fax
 www.eagletugs.com

EAGLE TT ALL WHEEL DRIVE AIRCRAFT TUGS

MODELS		TT-10 AWD	TT-12 AWD	
PERFORMANCE	Drive Wheels	2 Front / 4 Rear	2 Front / 4 Rear	
	*Drawbar Pull	10,000 lbs / 44 kN	12,000 lbs / 54 kN	
	*Towing Capacity 1st Gear	150,000 lbs / 68,100 kgs	180,000 lbs / 81,720 kgs	
	Service Weight Diesel	11,803 lbs / 5,365 kgs	13,350 lbs / 6,068 kgs	
	Optional Cab - Add	700 lbs / 318 kgs	700 lbs / 318 kgs	
DIMENSIONS	Length	134 in / 3,378 mm		
	Width	72 in / 1,829 mm		
	Width (dual rear)	72 in / 1,829 mm		
	Height	47 in / 1,194 mm		
	Height w/ cab (option)	74 in / 1,880 mm		
	Wheelbase	87 in / 2,210 mm		
	Track	51 in / 1,295 mm		
	Tires (front+rear)	9.5 x 16.5 in		
	Step Height	10 in / 254 mm		
	Ground Clearance	9 in / 228 mm		
CHASSIS	Frame/Body	.500 in / 12.7 mm thick A36 steel		
	Bumper-Front/Rear	4 in / 101.6 mm thick A36 steel		
TRAVEL	Suspension	Leaf springs over both axles		
	Number of Speeds	3 forward / 1 reverse with neutral safety switch		
	Max Speed	13 mph / 20.9 kph		
	Steering	Hydraulic power-boosted mechanical: self-centering		
	Brakes	Hydraulic, self-adjusting split type with accumulator		
	Front Brakes	13 in (disc)		
	Rear Brakes	12 x 3 in (drum)		
	Parking Brakes	Orscheln-type mechanical to rear brake drums		
ENGINE OPTIONS		DIESEL**		
SPECIFICATIONS	Manufacturer	Yanmar		
	Model	4TNV98T		
	Rated Output @ 2800 rpm	84 HP / 62 kW		
	Torque @ 2800 rpm	234 ft lbs / 317 Nm		
	Cylinders - Displacement	4 Cylinder / 3.3 L		
	Fuel Tank	18 gallons / 68 liters		
	Air Cleaner	Severe environment, heavy duty, dry replacement element		
ELECTRICAL	System	12 Volt		
	Alternator	80 amp		
	Battery (cold crank)	650 amp		
	Ignition	Keyed with anti-restart switch		
	Lights	Dual Halogen headlights / combination brake, tail and back-up at rear-all recessed		
	Instruments	Dual-unit digital back-lit display offering engine diagnostics and full instrumentation		

SOLD & SERVICED BY:

* Rated at .9 COF, 0% grade. ** EPA emissions compliant.