

HOBO Energy Logger

Multi-channel energy data logging system



The Multi-Channel HOBO Energy data logger is a modular, reconfigurable data logging system for energy and industrial monitoring applications.

The 15-channel system enables energy and facility management professionals to quickly and easily solve a broad range of monitoring applications without having to purchase a toolbox full of data loggers.

Supported Measurements:

Temperature, Relative Humidity, Dew Point, 4-20mA, AC Current, AC Voltage, Air Velocity, Amp Hour, Carbon Dioxide, Compressed Air Flow, DC Current, DC Voltage, Differential Pressure, Gauge Pressure, Kilowatt Hours, Kilowatts, Power Factor, Pulse Input, Volatile Organic Compound, Volt-Amp Reactive, Volt-Amp Reactive Hour, Volt-Amps, Water Flow, Watt Hours, Watts, Wind

Key Advantages:

- Records up to 15 channels
- Provides 12v excitation for third-party sensors
- Pre-configured Smart Sensors for fast setup
- Signal conditioning modules retain configurations until you change them, providing plug-and-play convenience for commonly used sensors
- Power options include battery operation or AC power adapter
- Works with Onset's E50B2 Power & Energy Meter to measure Power Factor, Reactive Power, Watt Hours, and more

Minimum System Requirements:



Software
See pg 37



Interface
Cable*



Sensor
See pg 41

► For complete information and accessories, please visit: www.onsetcomp.com

Part number	H22-001
Memory	512K nonvolatile flash data storage
Operating Range	-20° to 50°C (-4° to 122°F) with alkaline batteries -40° to 60°C (-40° to 140°F) with lithium batteries
Sensor Inputs	6 RJ-12 Smart Sensor jacks plus 3 FlexSmart module slots
Communication	RS-232 via 3.5 mm serial port*
Logging Interval	1 second to 18 hours, user-specified interval
Sensor Excitation	12 V DC at 200 mA total, with user-programmable warm up time on a per-channel basis
Battery Life	1 year typical
Battery Type	8 standard AA alkaline batteries (included)
External Power	Supports optional 13.6 V DC regulated AC Wall Adapter Connector
Time Accuracy	0 to 2 seconds for the first data point and ± 5 seconds per week at 25°C (77°F)
Dimensions	15.6 cm x 8.4 cm x 4.6 cm (6.13 in x 3.31 in x 1.81 in)
CE Compliant	Yes

*USB to Serial interface cable, part #CABLE-PC-3.5, see page 45