



REDBOX
INTERNATIONAL

TWIN RB75A

MODEL TWIN RB75A

HAND / AIR PORTABLE POWER UNIT FOR AIRCRAFT AND COMBAT VEHICLES



SUPPLIED WITH UNIT

2 x Charger
Output Cable
Parallel Joining Cable
Twin Trolley
2 x Thermal Protection Bag

OPTIONAL EXTRAS

Various output cable lengths
Croc Clips
Various Connectors
25A, 50A, 75A or 100A 28V DC power supply

TWIN RB75A	
Max amps	3500 (Nom. short circuit current) 5200 (Max. short circuit current)
Capacity	76 Amp Hrs @ 10 hr rate
Max Voltage	26V DC
Size (cm)	2 X L 45 x W 10 x H 38
Weight kg	70
Operating Temp.	-40°C - +60°C
Case	Stainless steel
Voltage indication	Digital to IP65
Auxiliary Protection	Circuit breaker 40A
Output Cable	2m heavy duty cable with aircraft connector
Charger	2 X 8 A Electronic universal AC input. Charging time less than 2 hours from 50%
Protection	Reverse polarity warning

- *Totally weather protected.*
- *Air transportable, 'Non Hazardous'*
- *Maintenance free.*
- *Tough and compact.*
- *No memory effect.*
- *Works in any orientation.*
- *High charge retention.*
- *Long shelf life.*
- *Fast recharge.*
- *External charger for prolonged unit life.*
- *No cycling.*
- *Leak proof.*
- *Cells replaceable on condition.*
- *Heavy duty engine starting of turbo prop, turbine, aircraft and helicopters.*
- *Starts Main Battle Tanks.*
- *Starts Armoured Fighting Vehicles.*
- *Lightweight portable start power at remote locations.*

